# **SELF PRIMING** RTFUGAL

- ■SELF-PRIMING PUMP requires no water for subsequent pumping operation once initial pumping is done, and the pumping capacity is large.
- ■EFFICIENT, ECONOMICAL OPERATION is assured by directly coupled pump. It provides compactness and guarantees that power is not lost.
- ■WATER-RESISTING QUALITIES are prominent by adopting mechanical seal and the impellers which are made of special cast iron.
- ■HIGHLY ADVANCED ROBIN GASOLINE ENGINE, which is powerful and durable ensures easy maintenance and trouble-free operation.

# Model PTD306/PTD406/PTD405





### PERFORMANCE CURVE 160 (ft) 140 40 120 Total Head 30 PTD406 PTD405 40 10 20 PTD306 1,000 1,500 2,000 500 100 200 300 400 500 600 Pumping Capacity (U.S. gal / min)

## STANDARD ACCESSORIES



The left picture shows typical samples. Material and design may vary by models.


## OPTION Available for PTD405



## Model PTK206/PTK306



## PERFORMANCE CURVE



## STANDARD **ACCESSORIES**



The above picture shows typical samples. Material and design may vary by models.

## **SPECIFICATIONS**

Model			PTD306	PTD406	PTD405
PUMP	Туре		Self-priming, Centrifugal pump		
	Suction × Delivery Diameters		76.2×76.2mm(3×3in.)	101.6×101.6mm(4×4in.)	101.6×101.6mm(4×4in.)
	Total Head		28m	27m	24m
	Maximum Delivery Volume		900 @/min	1300 @/min	1800 @/min
	Suction Head		8m		
	Axle Seal Material(Mechanical Seal)		Ceramic-carbon		
	Model		DY23-2D	DY27-2D	DY35D
끸	Туре		Robin Air-cooled, 4-stroke, Diesel engine		
ENGINE	Fuel		Diesel light oil		
EN	Fuel Tank Capacity		3.2L		4.5L
	Starting System		Recoil starter		Hand cranking (Recoil starter as option)
	Dimensions (L×W×H)  Net Weight  Standard Accessories		590×410×510mm	680×410×590mm	685×485×592mm
			43.5kg	52.2kg	69.6kg
			Engine tool kit (1 set), Strainer (1 pc.), Hose coupling (2 pcs.), Hose band (3 pcs.)		
W	ith Wheel	Dimensions (L×W×H)	-		970×685×720mm
Kit	& Stand	Net Weight			76.6kg

PTK206	PTK306			
Self-priming, C	entrifugal pump			
50.8×50.8mm(2×2in.)	76.2×76.2mm(3×3in.)			
23	3m			
520 @/min	800 @/min			
8m				
Ceramic-carbon				
EY15-3DK	EY20-3DK			
Robin Air-cooled, 4-stroke, Kerosene engine				
Kerosene (Automobile gasoline for starting)				
Kerosene 2.6L Gasoline 0.13L	Kerosene 3.4L Gasoline 0.17L			
Recoil starter				
470×355×419mm	527×379×422mm			
24kg	27.5kg			
Engine tool kit (1 set), Strainer (1 pc.), Hose coupling (2 pcs.), Hose band (3 pcs.)				
_	_			